

NTC Series NTC2 Air and Gas Temperature Sensor



The NTC2 Series of High Performance Temperature Sensors are designed to measure the temperatures of all types of air and gas in demanding motorsport and automotive testing applications.

The sensing element can either be a PT1000 or a NTC 3KΩ Thermistor, calibration of each is well defined and can be installed into most common ECUs and data logging systems.

Construction choice is either anodised aluminium, brass or stainless steel — all with a heat insulating PEEK ISOTIP which isolates the sensing element from surrounding heat soak. With standard motorsports cable and sleeve this will protect from the harsh environments around the vehicle.

Technical Specifications

Ranges (FS)	-30°C to +150°C
Accuracy	±1°C
Response Time	<5 Seconds
Seal	Viton O-Ring
Sensor Time	NTC 3KΩ or PT1000
Construction	Brass, Aluminium or Stainless Steel with PEEK ISOTIP
Electrical Connection	100cm, 26AWG 55Spec + DR25 Sleeve
Mechanical Connection	M6x1, M8x1 or M10x1
Protection Class	IP67
Weight (Excluding Cable)	5g to 10g (Depending on Material)

	NTC 10KΩ	PT1000
Temp °C	Output Ω	Output Ω
-30	53100.00	882.20
-20	29121.00	921.60
-10	16599.00	960.90
-0	9795.00	1000.00
10	5970.00	1039.00
20	3747.00	1077.90
25	3000.00	1097.30
30	2417.10	1116.70
40	1598.10	1155.40
50	1080.90	1194.00
60	746.40	1232.40
70	525.60	1270.80
80	376.50	1309.00
90	274.59	1347.10
100	203.46	1385.10
110	153.09	1422.90
120	116.79	1460.70
130	90.28	1498.30
140	70.58	1535.80
150	55.79	1573.30

bf1systems adopts a continuous development program which sometimes necessitates specification changes without notice.

Features

- Fast Response
- With PEEK ISOTIP
- -30°C to +150°C
- NTC or PT1000
- Rugged Construction

Applications

- Air Intake
- Cabin Temperature

Contact Us:

bf1systems
Unit 13 Springfield Business
Park
Priest Court
Grantham
Lincolnshire
NG31 7FZ
United Kingdom

+44 (0)1476 568057
sales@bf1systems.com


Part Number Configuration

Mounting Thread




Construction

Sensor Type

Special Code



Mechanical Details



Maximum Torque Rating

Thread	Material	Max. Torque (Nm)
M6	Aluminium	1.5
	Stainless Steel	5
M8	Aluminium	8
	Stainless Steel	10
M10	Aluminium	10
	Brass	10
	Stainless Steel	15

bf1systems

The Competitive Advantage

Features

- Fast Response
- With PEEK ISOTIP
- -30°C to +150°C
- NTC or PT1000
- Rugged Construction

Applications



- Air Intake
- Cabin Temperature

Contact Us:

bf1systems
Unit 13 Springfield Business
Park
Priest Court
Grantham
Lincolnshire
NG31 7FZ
United Kingdom

+44 (0)1476 568057
sales@bf1systems.com

Temperature Vs Resistance Graphs



Features


- Fast Response
- With PEEK ISOTIP
- -30°C to +150°C
- NTC or PT1000
- Rugged Construction

Applications

- Air Intake
- Cabin Temperature

Connection Details

Output	Output
Red	White



Contact Us:

bf1systems
 Unit 13 Springfield Business
 Park
 Priest Court
 Grantham
 Lincolnshire
 NG31 7FZ
 United Kingdom

+44 (0)1476 568057
 sales@bf1systems.com